



- New flat heater in models 30–120 l
- Suitable for installation in restricted areas, it can be built in the kitchen line
- Quick water heating due to the concept of two vessels
- It combines the traditional DZD technology and modern design
- Possible alternatives to the replacement of the gas heater
- The option of purchasing 2 multipurpose holders (order number 102000703)



Types of storage tanks		OKHE ONE 30	OKHE ONE 50	OKHE ONE 80	OKHE ONE 100	OKHE ONE 120
Order number		181110801	180510801	180110801	180810801	180310801
Capacity	[l]	28	45	65	80	98
Max. weight of the empty water heater	[kg]	22	31	46	55	62
Insulation thickness	[mm]	min. 33				
Thermal conductivity of the insulation	[W·m ⁻¹ ·K ⁻¹]	0,021				
Power consumption of the el. heating unit	[W]	1100	2000			
Heating time from 10 °C to 60 °C	[h]	1,5	1,5	2,0	2,5	3,0
Electrical connection		1/N/PE ~ 230V/50Hz				
Recommended circuit breaker size	[A]	10	16			
Degree of protection		IP44				
Max. working temperature / overpressure in tank	[°C]/[bar]	90/6				
Energy efficiency class		C				
Annual consumption	[kWh·a ⁻¹]	561	1353	1378	1404	1403

Dimensions [mm]	A	B	D	E	F	H	K	R
OKHE ONE 30	617	318	523	500	350	110	110	180
OKHE ONE 50	845	318	523	730	560	110	110	180
OKHE ONE 80	1112	318	523	920	750	190	110	180
OKHE ONE 100	1327	318	523	1135	950	190	110	180
OKHE ONE 120	1552	318	523	1360	1150	190	110	180

